

OUTLANDER™ 800 H.O. EFI



**Outlander
800 H.O. EFI 4x4**



**Outlander
800 H.O. EFI 4x4 XT**



**Outlander Max
800 H.O. EFI 4x4**



**Outlander Max
800 H.O. EFI 4x4 XT**

	SPECIFICATIONS	OUTLANDER 800 H.O. EFI 4X4	OUTLANDER MAX 800 H.O. EFI 4X4
ENGINE	Type	800cc, 4-stroke, V-twin, liquid cooled, 4-valve OHC	800cc, 4-stroke, V-twin, liquid cooled, 4-valve OHC
	Bore & Stroke	91 x 62 mm	91 x 62 mm
	Torque	73 Nm@ 5,500 RPM	73 Nm@ 5,500 RPM
	Fuel Delivery	EFI, 46mm Throttle Body, 2 Siemens [†] VDO injectors	EFI, 46mm Throttle Body, 2 Siemens [†] VDO injectors
	Starting System	Electric	Electric
	Transmission	CVT, sub-transmission with high, low, park, neutral & reverse	CVT, sub-transmission with high, low, park, neutral & reverse
	Drive Train	Selectable 2x4/4x4 shaft driven with Visco-Lok [†] front differential	Selectable 2x4/4x4 shaft driven with Visco-Lok [†] front differential
CHASSIS	Frame	SST™	SST™
	Front Suspension Type	Double A-arm, Forged Aluminum upper arm, 8 in (203 mm)	Double A-arm, Forged Aluminum upper arm, 8 in (203 mm)
	Travel		
	Rear Suspension Type	TTI™ independent	TTI™ independent
	Travel	9 in (228.6 mm)	9 in (228.6 mm)
	Front Brake	2 inboard hydraulic discs	2 inboard hydraulic discs
	Rear Brake	1 inboard hydraulic disc	1 inboard hydraulic disc
	Front Tires	26 x 8 x 12 in (660.4 x 203 x 305 mm)	26 x 8 x 12 in (660.4 x 203 x 305 mm)
Rear Tires	26 x 10 x 12 in (660.4 x 254 x 305 mm)	26 x 10 x 12 in (660.4 x 254 x 305 mm)	
DIMENSIONS	L x W x H	86 x 46 x 45 in (2,184 x 1,168 x 1,143 mm)	94 x 46 x 45 in (2,387 x 1,168 x 1,143 mm)
	Wheelbase	51 in (1,295 mm)	59 in (1,499 mm)
	Dry Weight	639 lbs (290 kg)	689 lbs (313 kg)
	Ground Clearance	12 in (305 mm)	12 in (305 mm)
	Seat Height	34.5 in (877 mm)	34.5 in (877 mm)
	Rack capacity (Front & Rear)	Front: 100 lbs (45 kg) Rear: 200 lbs (90 kg)	Front: 100 lbs (45 kg) Rear: 200 lbs (90 kg)
	Towing Capacity	1,300 lbs (590 kg)	1,300 lbs (590 kg)
	Fuel Capacity	5.3 US gal (20L)	5.3 US gal (20L)
FEATURES	Instrumentation	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeter, fuel, gear position, 4x4 indicator, diagnostics, auto shut off	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeter, fuel, gear position, 4x4 indicator, diagnostics, auto shut off
	Anti-theft	D.E.S.S. (digital encoded security system)	D.E.S.S. (digital encoded security system)
	Storage	Rear storage 5.3 US gal (20L)	Rear storage 5.3 US gal (20L) CRS (Convertible Rack System)
	Electrical	Prewired for winch	Prewired for winch
	Lighting	2 fender mounted headlamps (35W) with tail light/brake light	2 fender mounted headlamps (35W) with tail light/brake light
	DC Outlet	Lighter type in console, Standard connector in the back (15A)	Lighter type in console, Standard connector in the back (15A)
	XT Package Content Available	BRP XL2500 winch by Warn [†] , roller fairlead, wired remote control, cast aluminum rims, aggressive tread Carlisle [†] ACT radial tires, heavy duty front & rear bumpers, handguards	BRP XL2500 winch by Warn [†] , roller fairlead, wired remote control, Ltd Edition cast aluminum rims, aggressive tread Carlisle [†] ACT radial tires, heavy duty front & rear bumpers, handguards
Available Colors	Yellow (XT only), Laurentian Green, Viper Red	Yellow, Laurentian Green, Viper Red	

©2006 Bombardier Recreational Products Inc (BRP). All rights reserved.™® and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Can-Am™ Outlander MAX ATVs: These ATVs are recommended for drivers aged 16 and older, and passengers aged 12 and older only.

can-am



OUTLANDER™ 800 H.O. EFI (EC)



**Outlander
800 H.O. EFI 4x4**



**Outlander
800 H.O. EFI 4x4 XT**



**Outlander Max
800 H.O. EFI 4x4**



**Outlander Max
800 H.O. EFI 4x4 XT**

	SPECIFICATIONS	OUTLANDER 800 H.O. EFI 4X4 (EC)	OUTLANDER MAX 800 H.O. EFI 4X4 (EC)
ENGINE	Type	800cc, 4-stroke, V-twin, liquid cooled, 4-valve OHC	800cc, 4-stroke, V-twin, liquid cooled, 4-valve OHC
	Bore & Stroke	91 x 62 mm	91 x 62 mm
	Net Power	< 15kW (EC version only)	< 15kW (EC version only)
	Fuel Delivery	EFI, 46mm Throttle Body, 2 Siemens [†] VDO injectors	EFI, 46mm Throttle Body, 2 Siemens [†] VDO injectors
	Starting System	Electric	Electric
	Transmission	CVT, sub-transmission with high, low, park, neutral & reverse	CVT, sub-transmission with high, low, park, neutral & reverse
	Drive Train	Selectable 2x4/4x4 shaft driven with Visco-Lok [†] front differential	Selectable 2x4/4x4 shaft driven with Visco-Lok [†] front differential
	CO Emissions Exhaust System	EURO 2 approved Air injection system/Catalyst	EURO 2 approved Air injection system/Catalyst
CHASSIS	Frame	SST™	SST™
	Front Suspension Type	Double A-arm, Forged Aluminum upper arm, 8 in (203 mm)	Double A-arm, Forged Aluminum upper arm, 8 in (203 mm)
	Travel		
	Rear Suspension Type	TTI™ independent	TTI™ independent
	Travel	9 in (228.6 mm)	9 in (228.6 mm)
	Front Brake	2 inboard hydraulic discs	2 inboard hydraulic discs
	Rear Brake	1 inboard hydraulic disc	1 inboard hydraulic disc
Front Tires	26 x 8 x 12 in (660.4 x 203 x 305 mm)	26 x 8 x 12 in (660.4 x 203 x 305 mm)	
Rear Tires	26 x 10 x 12 in (660.4 x 254 x 305 mm)	26 x 10 x 12 in (660.4 x 254 x 305 mm)	
DIMENSIONS	L x W x H	86 x 46 x 45 in (2,184 x 1,168 x 1,143 mm)	94 x 46 x 45 in (2,387 x 1,168 x 1,143 mm)
	Wheelbase	51 in (1,295 mm)	59 in (1,499 mm)
	Dry Weight	649 lbs (295 kg)	699 lbs (318 kg)
	Ground Clearance	12 in (305 mm)	12 in (305 mm)
	Seat Height	34.5 in (877 mm)	34.5 in (877 mm)
	Rack capacity (Front & Rear)	Front: 100 lbs (45 kg) Rear: 200 lbs (90 kg)	Front: 100 lbs (45 kg) Rear: 200 lbs (90 kg)
	Towing Capacity Fuel Capacity	1,300 lbs (590 kg) 5.3 US gal (20L)	1,300 lbs (590 kg) 5.3 US gal (20L)
FEATURES	Instrumentation	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeter, fuel, gear position, 4x4 indicator, diagnostics, auto shut off	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeter, fuel, gear position, 4x4 indicator, diagnostics, auto shut off
	Anti-theft	D.E.S.S. (digital encoded security system)	D.E.S.S. (digital encoded security system)
	Storage	Rear storage 5.3 US gal (20L)	Rear storage 5.3 US gal (20L) CRS (Convertible Rack System)
	Electrical	Prewired for winch	Prewired for winch
	Lighting	2 fender mounted headlamps (35W) with tail light/brake light – EC approved, 4 flashers	2 fender mounted headlamps (35W) with tail light/brake light – EC approved, 4 flashers
	Warning Signal	Horn	Horn
	DC Outlet	Lighter type in console, Standard connector in the back (15A)	Lighter type in console, Standard connector in the back (15A)
	XT Package Content Available	BRP XL2500 winch by Warn [†] , roller fairlead, wired remote control, cast aluminum rims, aggressive tread Carlisle [‡] ACT radial tires, heavy duty front & rear bumpers, handguards	BRP XL2500 winch by Warn [†] , roller fairlead, wired remote control, Ltd Edition cast aluminum rims, aggressive tread Carlisle [‡] ACT radial tires, heavy duty front & rear bumpers, handguards
Available Colors	Yellow (XT only), Laurentian Green, Viper Red	Yellow, Laurentian Green, Viper Red	

©2006 Bombardier Recreational Products Inc (BRP). All rights reserved.™ and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates.†Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Can-Am™ Outlander MAX ATVs: These ATVs are recommended for drivers aged 16 and older, and passengers aged 12 and older only.

can-am

